

Champion FL129



Volume: 129 litres or 4.5 cu. Ft.

Internal dimensions: 457mm x 457mm or 610mm or
18" x 18" x 24" (width x depth x height)

Power: 9KW, 39 Amps

Requires: An isolator with a minimum of a 40 Amp fuse

Phase: Can be single or three phase – to suit your supply

Max temp: 1300°C

External dimensions: 876mm x 991mm x 1727mm or
34.5" x 39" x 68" (width x depth x height)



Price includes:

- ST215 controller – a user friendly British controller, offering; 16 programs with 32 segments per program.
- 4 kiln shelves
- Generous selection of props
- Batt wash

Key features:

- Hand finished 6mm frame work with our Cool sides, allowing the frame to breathe and minimising condensation within the kiln, aiding longevity.
- Industrial grade elements housed in recessed brick.
- 1400°C hard brick again to aid longevity.
- R type .25 mm thermocouple.
- Floor mounted design with integral stand, with choice of hearth height.
- 190 mm of premium insulation for efficiency
- Door hinged left or right, to suit you.
- Manual damper, lever operated from the side.
- Manufactured by our team of engineers in Lancashire.
- Full testing and quality assurance checks are undertaken prior to delivery.
- Meaningful 2 year guarantee (excluding wear parts)
- Free helpline to help you to achieve the results you want.

Available with our VIP delivery, whereby we deliver the kiln into position, install, wire into your isolator, demonstrate the kiln and controller, leaving you confident and ready to fire.