

Champion FL772



Volume: 772 litres or 27 cu. Ft.

Internal dimensions: 914mm x 914mm or 914mm or
36" x 36" x 36" (width x depth x height)

Power: 49KW, 213 Amps

Requires: An isolator with a minimum of a 220 Amp fuse

Phase: Three phase, neutral and CPC supply

Max temp: 1300°C

External dimensions: 1334mm x 1448mm x 1727mm or
52.5" x 57" x 68" (width x depth x height)



Price includes:

- ST535 controller – a user friendly British controller, offering; 32 programs with 32 segments per program.
- 4 kiln shelves
- Generous selection of props
- Batt wash

Key features:

- Hand finished 6mm frame work with our Cool sides, allowing the frame to breathe and minimising condensation within the kiln, aiding longevity.
- Industrial grade elements housed in recessed brick.
- 1400°C hard brick again to aid longevity.
- R type .25 mm thermocouple.
- Floor mounted design with integral stand, with choice of hearth height.
- 190 mm of premium insulation for efficiency
- Door hinged left or right, to suit you.
- Manual damper, lever operated from the side.
- Manufactured by our team of engineers in Lancashire.
- Full testing and quality assurance checks are undertaken prior to delivery.
- Meaningful 2 year guarantee (excluding wear parts)
- Free helpline to help you to achieve the results you want.

Available with our VIP delivery, whereby we deliver the kiln into position, install, wire into your isolator, demonstrate the kiln and controller, leaving you confident and ready to fire.