

# EZ Fire Pro FL226



**Volume:** 226 litres or 7.9 cu. Ft.

**Internal dimensions:** 572mm x 572mm or 686mm or  
22.5" x 22.5" x 27" (width x depth x height)

**Power:** 16Kw, 69 Amps

**Requires:** An isolator with a minimum of an 80 Amp fuse

**Phase:** Three phase, neutral and CPC supply.

**Max temp:** 1300°C

**External dimensions:** 953mm x 1118mm x 1727mm or  
37.5" x 44" x 68" (width x depth x height)



## Price includes:

- ST535 controller – a user friendly British controller, offering; 32 programs with 32 segments per program.
- 4 kiln shelves
- Generous selection of props
- Batt wash

## Key features:

- Hand finished 6mm frame work with our Cool sides, allowing the frame to breathe and minimising condensation within the kiln, aiding longevity.
- Industrial grade elements housed in recessed brick.
- R type .25 mm thermocouple.
- Floor mounted design with integral stand, with choice of hearth height.
- 140 mm of premium insulation for efficiency
- Door hinged left or right, to suit you.
- Manual damper, lever operated from the side.
- Manufactured by our team of engineers in Lancashire.
- Full testing and quality assurance checks are undertaken prior to delivery.
- Meaningful 2 year guarantee (excluding wear parts)
- Free helpline to help you to achieve the results you want.

Available with our VIP delivery, whereby we deliver the kiln into position, install, wire into your isolator, demonstrate the kiln and controller, leaving you confident and ready to fire.