

# Chieftain TL76



**Volume:** 76 litres or 2.65 cu. Ft.

**Internal dimensions:** 460mm x 460mm or 18" x 18"  
(diameter x height)

**Power:** 6KW, 26 Amps

**Requires:** An isolator with a minimum of a 30 Amp fuse

**Phase:** Single

**Max temp:** 1300°C

**External dimensions:** 724mm x 826mm x 838mm or  
28.5" x 32.5" x 33" (width x depth x height)



## Prices includes:

- ST215 controller – a user friendly British controller, offering; 16 programs with 32 segments per program.
- 4 kiln shelves
- Generous selection of props
- Batt wash

## Key features:

- 0.9mm stainless steel wrap
- Stainless steel lid – the only top loading kiln on the market to offer this, giving greater life expectancy and reduced energy wastage.
- Industrial grade elements housed in recessed brick.
- R type .25 mm thermocouple.
- Full box section sub frame for added kiln strength and longevity.
- Fitted with 4 quality castors for easy mobility when required.
- Gas strut assisted lid opening for greater comfort.
- Manufactured by our team of engineers in Lancashire.
- Full testing and quality assurance checks are undertaken prior to delivery.
- Meaningful 2 year guarantee (excluding wear parts)
- Free helpline to help you to achieve the results you want.

Available with our VIP delivery, whereby we deliver the kiln into position, install, wire into your isolator, demonstrate the kiln and controller, leaving you confident and ready to fire.